



NOTE: PRECAST DROP MANHOLE BASE CAN ONLY BE USED FOR 8" PVC SDR-35 PIPE
 ENCASUREMENT OF DROP ASSEMBLY TO BE DONE BY OTHERS OUTSIDE DROP ASSEMBLY
 (SEE DWG. #SA05A)

- SPECIFICATIONS
- MINIMUM CONCRETE STRENGTH 4000 PSI. @28 DAYS (NJ DOT CLASS B)
- STEEL REINFORCEMENT-ASTM A185 VERTICAL WALLS 0.12 IN²/VERTICAL FOOT.
 HORIZONTAL BASE SLAB 0.12 IN²/HORIZONTAL FOOT.(1 1/2 MINIMUM CONCRETE COVER)
- MANHOLE DESIGN SPECIFICATIONS CONFORM TO "PRECAST REINFORCED CONCRETE MANHOLE SECTIONS" ASTM C478, LATEST REVISION

**Continental
 Concrete
 Products, Inc.**
 1 South Grosstown Rd.
 Pottstown, PA 19464
 Phone: (610) 327-3700
 Fax: (610) 327-9488

**48" DIA. SANITARY DROP MANHOLE BASE
 W/ PRECAST CHIMNEY FOR 8" PVC**

SIGNATURE OF APPROVAL

NJ48 DROP RISER